


# DVC301

Efficiency through a wide range of variants



**Deutronic Transportation / Logistics**  
Durable, future-proof and sustainable

To cover a very wide range of applications, Deutronic offers DVC standard vehicle converters for input voltages of 24V, 48V or 80V as well as 12V to 24V at the output. The robust design allows the use especially in harsh environments such as logistics, industrial trucks, railroad applications or electric vehicles. The DC/DC converters can also be used in a wide range of applications thanks to the customer-specific adaptation options such as an inhibit function.


Power .....



**DEUTRONIC**   
EDWANZ group

# DVC301

Efficiency through a wide range of variants



## Advantages

- ✓ Wide range of applications due to numerous voltage variants
- ✓ Optimized redesign of the proven DVC251 converter
  - Increased performance with reduced dimensions
  - Efficiency due to high effectiveness
- ✓ Ideal for applications such as logistics, industrial trucks, railroad applications or electric vehicles
- ✓ Highest safety due to IP67 degree of protection according to EN 60529
- ✓ DC/DC wide range input
- ✓ Galvanic separation 1,5kV (500V at 12/24VDC input voltage)

## Technical data

Type	Output power	Input voltage	Output voltage	Max. output current
DVC301-48-24	300W	48VDC	24VDC	12,5A



Deutronicstraße 5 | D-84166 Adlkofen/Germany | Tel. +49 8707 920-0  
E-Mail: [sales@deutronic.com](mailto:sales@deutronic.com) | [www.deutronic.com](http://www.deutronic.com)

